

TECHNICAL SPECIFICATIONS



Tiles sold by KINELE GROUP, SL. under the brand name KINELE for flooring use meet the following European standards and specifications:

DIMENSIONS	33.33cm x 33.33cm x 1cm
WEIGHT	9Kg/m ²
PACK SIZE	9 tiles per carton = 1m ² = 10.76 sq ft
INSTALLATION	Interlocking system-no adhesive required
COMPOSITION	Thermoplastique PVC. Contains no hazardous materials. Recyclable.
TOXICOLOGY	Non-toxic, biologically inert, no latex.
FIRE RATING	UNE.EN.13501-1:2002/B _{FL-s2} . M2 in accordance with European standard UNE 23.727.90 No restrictions on materials used to extinguish a fire.
COEFFICIENT OF EXPANSIONS	0.015% per °C=0.05mm per °C. D=0.00015
STORAGE/PACKING	Avoid heat and keep away from flames. Store below 120°C (248°F) to maintain the material in optimal condition. No specific packing requirements.
ELECTRICAL CONDUCTIVITY	Electricity insulation to 15000 volts
RESISTANCE	17.5Mpa
ABRASIVE RESISTANCE	Taber test- Weight loss of 12 mg (1kg, 1000 cycles, cloth CS17). Compare abrasive weight loss to other materials: 50 mg for a conventional wooden floor 30 mg for a high standing wooden floor 25 mg for a varnish
INSTALLATION	On level and strong subfloor. Carefully read the instruction guide.
CLEANING	Use water and standard cleaning products. Do not use ammonia based cleaning products or corrosive products like acid.
WARRANTY	2 years product warranty due to a manufacturing flaw.

Contact us:

www.kinele.com

Email: info@kinele.com

Free Phone Europe 00 800 00454 6353

Toll free USA and Canada 1-866-4kinele (1-866-454-6353)