

TECHNICAL INFORMATION



TECHNICAL INFORMATION RUBBER RING MATS

COMPOSITION	100% natural rubber
FORMAT	TILE: 1,00m x1,50m CARPET:0,9m x1,50m DOORMAT:1,00 x0,60m
THICKNESS	TILE: 2,3cm CARPET:1,4cm DOORMAT:1,3 cm
WEIGHT	TILE: 11,33kg/sqm (17kg/tile) CARPET:7,77kg/sqm(10,5kg/tile) DOORMAT:5,83kg/sqm (3,5kg/tile)
DENSITY	1,17 +-0,04
HARDNESS	62 +- 3 (SHORE A)
ELONGATION	300%
IDENTIFICATION OF DANGER	Do not contain toxic nor dangerous products
FIRE CLASSIFICATION	UNE 23.727.90: Class M-3
EXTINCTION AND DECOMPOSITION	All types of extinction allowed. No incompatibility.
STORAGE AND PACKING	Avoid heat and keep away from flames. Do not heat above 80°C. All types of packing allowed.
TEMPERATURE RESISTANCE	From -50°C to 80°C
ELECTRICAL CONDUCTIVITY	11,74 according to norm DIN VDE 0303 part 2
TOXICOLOGY AND ECOLOGY	No risk for human nor environment. Recyclable.
CLEANING	Water. Do not use ammonia based cleaning products or corrosive products like acid.
WARRANTY	2 years product warranty due to a manufacturing flaw

Information above mentioned contain approximated values that may vary according to production process and tolerance.